



Corseal 917, Anti-Rust

Dry to Touch Inhibitor

Corseal 917 is a thin film corrosion inhibitor for all types of metal surfaces. Prevents rust, oxides, stains, and discoloration. 917 is also a penetrant for loosening rusted and corroded parts. Lubricates also. All metals.

Corseal 917 provides moisture and water displacing properties. When used in a dip tank, water or moisture is displaced, lifted and settled to the bottom of the dip tank for easy removal.

Corseal 917 is non-oily, providing a micro-thin film, provides no or very mild odor and does not cause skin irritation.

Features & Benefits

- Dry to touch properties after 8-24 hours.
- Provides months of surface protection up to 6 months or more.
- Very high flash point over 200 F. Providing added safety.
- Prevents finger print stains or etching.
- Allows for ease of final gauging and testing without oily films.
- Penetrates rusted bolts and parts.

Physical Data

pH	n/a
Product Type	Liquid
Spec. Gravity	0.832
lbs./gal.	6.94
Foam, 0 = Low, 9 = High	0
Shelf-Life Years	10 years
Freeze Information	Not damaged by freezing.

Typical Processing

1. Dip parts in solution. Drain as necessary. (or air blow down)
2. Spray on surfaces to loosen rusted locked bolts or parts, allow a soaking period, apply again if necessary.
3. If parts entering the tank are wet, drain water from the tank bottom periodically.



- Store parts away from high water vapor, dust and dirt, and fumes of gases, acids, or bleach.

Packaging

Container Type	Pails
Net Units	380
Tare Wt.	25 lb.
Gross Wt.	405
DOT_Name	Not regulated by D.O.T.
DOT Hazard	Not regulated.
Tarriff ID	

Use Parameters

Concentration Range	100%
Temperature Range	Room temperature.
Time Range	Dip or flood.
Agitation	As necessary.

Waste Disposal

Neutralize pH, remove fats, oils, grease and heavy metals.

Holding Tank Materials of Construction

Steel or stainless.

Other Information

It is important that the OSHA DATA, "Material Safety Data Sheet" be carefully read and reviewed with the users of this product. OSHA data is required to be posted in the work area by law.

WARRANTY: HUBBARD-HALL INC. IS NOT RESPONSIBLE FOR THE MISUSE, MISAPPLICATION, OR MISHANDLING OF THIS PRODUCT. SEE THE TERMS AND CONDITIONS OF SALE ON OUR WEBSITE FOR ADDITIONAL TERMS AND CONDITIONS CONCERNING OUR PRODUCTS, INCLUDING BUT NOT LIMITED TO, LIMITATIONS AND DISCLAIMERS OF WARRANTIES AND LIABILITIES.



Our People. Your Problem Solvers.

For more information on this process,
please call us at 203.756.5521 or email: techservice@hubbardhall.com

Hubbard-Hall holds certifications for **ISO 9001:2015**, Responsible Distribution, as accredited by the **ACD** (Alliance for Chemical Distributors) and as a **Women-Owned Small Business**, as well as maintaining an association with **Omni-Chem**¹³⁶.